

## EZMaker SDK Express (C725B)



Actual product image may vary from image shown.



- E-learning projection and presentation capture
- Surveillance system A/V feeds backup
- Video conferencing capture and backup

### Features

- Fully DirectShow compatible
- Support uncompressed video capture in AVI or WMV format
- Support snapshot in BMP or JPG format
- Capture and digitalize NTSC/PAL/SECAM analog signals
- Support multiple programming languages

### Support Software

- Microsoft DirectShow
- UStream Producer
- Adobe Flash Media Live Encoder 3
- Microsoft Windows Media Encoder 9
- Microsoft Express Encoder
- Real Producer(v13)
- CyberLink PowerDirector/PowerProducer
- GraphEdit
- AMCap
- XSplit
- Telestream Wirecast
- Corel VideoStudio

### Specifications

<b>Video Input</b>	S-Video, Composite video
<b>Audio Input</b>	RCA audio
<b>Video Resolution</b>	160×120 / 176×144 / 240×180 / 240×176 320×240 / 352×240 / 352×288 (PAL only) 640×240 / 640×288 / 640×480 704×576 (PAL only) / 720×240 / 720×288 720×480 / 720×576 (PAL only)
<b>Pixel Format</b>	YUY2(4:2:2), UYVY (4:2:2), RGB24 (4:4:4)
<b>Color Adjustment</b>	Brightness, Contrast, Hue, Saturation, Sharpness
<b>Multi-Card Support</b>	Yes (up to 8 cards)
<b>Programming Language</b>	VC, VB, Delphi, C#, VB.NET
<b>SDK Framework</b>	General DLL
<b>Operating Environment</b>	Temperature: 0 to 65°C Humidity: 15 to 80% RHNC
<b>Storage Environment</b>	Temperature: -30 to 65°C Humidity: 15 to 90% RHNC
<b>Power Requirement</b>	3.3V max 400mA
<b>Dimensions (mm)</b>	93.5(L)*68.78(W)*1.57(H)

### System Requirements

- **CPU**
  - Intel® Pentium® 4 3.0 GHz
  - AMD Athlon™ 64 3200+
- **VGA card with support for DirectX9.0c or above**
- **512 MB RAM**
- **PCI-E Slot**
- **Sound Card**
- **Windows® 8/7/XP (32/64-Bit)**