

IRU151-I

Robust RISC-based DIN-rail Fanless Embedded System with i.MX 6UL Processor, DIO (2-in/2-out), 4 AI Channels (16-bit, 100 S/s, ±20mA) and 2 PCIe Mini Card Slots

Features

- RISC-based (i.MX 6ULtralite) processor 528 MHz
- 512MB DDR3 SDRAM onboard
- 8GB eMMC flash onboard
- 2 PCI Express Mini Card slots (Wi-Fi, 3G/4G or LoRa)
- 4 isolated analog input channels (16-bit, 100 S/s, ±20mA)
- 1 isolated COM port
- 1 isolated DIO (2-in/2-out)
- Embedded Linux operating system (Yocto)
- Wide operating temperature range from -40°C to +70°C
- Supports LabVIEW versions later than 2016
- Supports OPC UA



Introduction

The IRU151-I DIN-rail fanless embedded system utilizes a low power RISC-based (i.MX6 UL) processor, one RS-232/422/485 serial port, one LAN, two digital input channels, two digital output channels, four analog input channels for measuring current, designed to withstand temperatures ranging from -40°C to +70°C for applications in extreme operating environment and industrial automation.

The IRU151-I is an Ethernet-based gateway supporting two wireless sockets (Wi-Fi, 3G/4G or LoRa), acting as a simple transparent interface between Ethernet-based network and Modbus devices such as meters, monitors, protective relays, trip units, motor controls and other devices that communicate using Modbus protocol.

Also, the IRU151-I can record digital/analog of devices and control digital devices. It can offer a simple, scalable web-based monitoring solution providing real-time data views, on-board data logging/trending, and simple control over Modbus devices. Embedded math function such as RMS and FFT are used to make advanced diagrams. The ready-to-run IRU151-I is specially designed for remote control/monitoring management applications ideal in a unmanned control room, an industrial machine, an automatic parking lot, a traffic cabinet, just to name a few.

Specifications

| | | |
|-------------------|---|---|
| Construction | Extruded aluminum and heavy-duty steel, IP40 | |
| CPU | NXP i.MX 6UL processor, ARM® Cortex®-A7 @ 528 MHz | |
| System Memory | 1 x DDR3-1600 onboard, 512 MB | |
| System I/O Outlet | Serial Port | 1 x RS-232/422/485 Magnetic isolation protection 2KV |
| | LAN | 1 x 10/100 Mbps Ethernet Magnetic isolation protection 1.5KV |
| Analog Input | 4 x AI (isolation) channels: 4 (differential) | Input impedance: 249Ω Input range: ±20mA Resolution: 16-bit Sampling rate : 100 S/s Overvoltage protection : ±55V Trigger source : analog or digital (software selectable) |
| | USB | 1 x USB 2.0 (type A) |
| DIO | 1 x DIO (2-in/2-out) with isolation 2KV DI: wet/dry DO: wet | |

| | | |
|-----------------------|--|--|
| System I/O Outlet | DIO | DI: Input channels: 2 source type Input voltage: 0 to 30 VDC digital input levels for dry contacts: -Logic level 0: close to GND -Logic level 1: open Digital input levels for wet contacts: -Logic level 0: +10V to +24V (DI to COM-) -Logic level 1: +3V max. DO: Output channels: 2, sink type Output current: max. 200 mA per channel On-state voltage: 24VDC nominal, open collector to 30V Optical isolation protection 2 KV |
| | Console Port | Yes For user setting with debug |
| | EEPROM | 1 x EEPROM (2 Kb) |
| | Device ID | ID setting 0 to 255 |
| Wireless | 2 x PCI Express Mini Card slot (only USB signal) 1 x SIM card socket | |
| | Watchdog Timer | 0.5 to 128 sec. with a time resolution of 0.5 sec. |
| RTC | Yes (RTC battery on board) | |
| LEDs | 2 x LED for dual wireless status 2 x LED for DI status 2 x LED for DO status | |
| Storage | 1 x eMMC 8GB flash onboard | |
| Power Supply | 9 to 48 VDC | |
| Operating Temperature | -40°C to +70°C (-40°F to +158°F) | |
| Storage Temperature | -45°C to +85°C (-49°F to +185°F) | |
| Humidity | 10% to 95% | |
| Vibration Endurance | 2 Gms @ (10 to 150Hz sine wave; operation) | |
| Dimensions | 55 mm (2.16") (W) x 82 (3.23") mm (D) x 108 (4.25") (H) | |
| Weight (net/gross) | 0.32 kg (0.71 lb)/0.53 kg (1.17 lb) | |
| Installation | DIN-rail | |
| Certifications | FCC part 15, Heavy Industrial CE | |

Wireless Specifications

| | | |
|--------------|--|---|
| 4G module | 4G Mini card LTE SIERRA AIRPRIME MC7304 (optional) | Standards: LTE Cat.3 Interface: USB Radio Band/ Frequencies (MHz): 850(5) / 900(8) / 1800(3) / 1900(2) @GSM 850(5) / 900(8) / 1900(2) / 2100(1) @UMTS 800(20) / 900(8) / 1800(3) / 2100(1) / 2600(7) @FDD LTE Region: Global |
| Wi-Fi module | Wi-Fi Mini card Sparklan WPEQ-160ACN (optional) | Qualcomm Atheros QCA9377-7 Antenna: 2 x UFL connectors, 1T1R Operating Frequency: 802.11 ac/a/b/g/n ISM Band 2.412 GHz to 2.472 GHz 5.180 MHz to 5.825 MHz Interface: USB Region: Global |
| 3G module | 3G Mini card Quectel UC20G (optional) | UMTS:800/ 850/ 900/ 1900/ 2100MHz GSM/EDGE 850/ 900/1800/ 1900MHz Region: Global |
| 4G module | 4G Mini card LTE RYR2800 (uBlox R280) (optional) | Standards: LTE Cat.1 Interface: USB Radio Band/ Frequencies (MHz): LTE bands1, 3,5,7,8,28) Region: TW, AU |
| | 4G Mini card LTE RYR2110 (uBlox R211) (optional) | Standards: LTE Cat.1 Interface: USB Radio Band/ Frequencies (MHz): LTE bands1, 3,7,20) Region: EU |

Software Specifications

| | |
|-----------------------|--|
| OS | Linux Kernel 3.14.52 Yocto FIDO 1.8 |
| Protocol Types | ICMP, TCP/IP, UDP, ARP, Telnet, SNMP, HTTP, HTTPS, SSL, SMTP, FTP, TFTP, NTP, DNS, PPP, PPPoE, DHCP, NFS |
| Software Types | Serial Server Supports TCP Server/TCP client/UDP/Pair/VC Supports IP filter Supports 32 TCP connections |
| | Modbus Supports Modbus TCP/Modbus RTU/Modbus ASCII Supports TCP for multiple COM port |
| Setting Configuration | SNMP Supports V1/V2C/V3 Supports SNMP Private MIB Supports read/write |
| | http /https Supports SSL Supports import/export Supports FW update |
| | Remote Manager Remote log Email SNMP Supports trap |
| Alert Function | Yes |

Ordering Information

| | |
|-----------------------------------|--|
| Standard | |
| IRU151-I-FL-DC | Robust DIN-rail fanless embedded system with i.MX 6UL processor, COM, LAN, DIO (2-in/2-out), 4 AI (16-bit,100 S/s, ±20mA) and 2 PCI Express Mini Card slot (-40°C to +70°C) |
| Optional | |
| Wireless (3G/GPS or Wi-Fi) module | |

Dimensions

