

Anti-glare Touch

GeneralTouch's Anti-glare Touch, based on proven surface acoustic wave (SAW) technology, uses special materials which greatly reduces the light reflection and increase the clarity under lighting. Anti-glare touch touchscreens can work under strong light with quick and accurate response. Because of the pure-glass structure, it has high light transmission. Provided with 5.4" to 42", this type of products is specially designed for applications in outdoor and strong-light environments.

Features:

- Strong-light resistance
- High light transmission
- Flat and consistent mechanical profile
- Easy and quick installation
- Touch with no excursion
- 5.4" to 42"
- 5-year warranty

Applications:

- Kiosk
- Ticketing machines
- Automations
- Vending machines
- Exhibition machines
- Banking machines

Anti-glare Touchscreen Specifications

MECHANICAL

Input Method	Finger or gloved hand (cloth, leather, or rubber) activation
Available Sizes	5.4" to 42"; other sizes can be custom-made

ELECTRICAL

Resolution	4096x4096
Touch Activation Force	80g or 120g
Controller	ST6001SU, ST6002SU, ST6201SU

OPTICAL

Light Transmission	90%
--------------------	-----

ENVIRONMENTAL

Temperature	Operating Temperature: -20°C~+50°C Storage Temperature: -40°C~+70°C
Relative Humidity	40°C at 90% RH, noncondensing
Altitude	3000m
Chemical Resistance	The touch active area of the touchscreen is resistant to chemicals that do not affect glass, such as: acetone, toluene, methyl ethyl ketone, isopropyl alcohol, methyl alcohol, ethyl acetate, ammonia-based glass cleaners, gasoline, kerosene, vinegar
Electrostatic Protection	Per EN 61000-4-2 meets: Contact discharge 4kV, air discharge 8KV
Agency Approvals	UL Systems incorporating GT touchscreens, controllers, and cables have been approved for CE marking. Systems incorporating GT touchscreens, controllers, and cables have been approved to FCC Class A compliance.

DURABILITY

Surface Durability	Surface durability is that of glass, Mohs' hardness rating of 7
Expected Life	No known wear-out mechanism, as there are no layers, coatings, or moving parts. Touchscreen technology has been operationally tested to more than 50 million touches in one location without failure, using a stylus similar to a finger.
Anti-Glare	Gloss :80± 15/100±15/60±15
Warranty	Touchscreen: 5-year limited warranty Controller: 3-year limited warranty

Go to www.generaltouch.com for more products and information, or contact us

GeneralTouch Technology Co.,LTD reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.